ASSESSORIES FOR FG-EVAC-500_AP



FG-EVAC-TFL2_AP END OF LINE DEVICES


PRODUCT OVERVIEW

The end of line device model **FG-EVAC-TFL2_AP** provides an accurate measurement of the impedance of the speaker line (400R/200R configurable load), in order to test the line integrity between the speakers and the PA/VA system. This allows to supervise the line until the last speaker without return cable, even when the line has smaller loads with just 1 or 2 speakers. It is a small device, very simple to install in 70V or 100V speaker lines and with a low power consumption. Several devices can be connected to the same speaker line. It is compatible both with **FG-EVAC-500_AP** systems with the latest firmware version.



- Supervision of 70V or 100V speaker lines.
- Easy connection and installation, surface mountable.
- Several devices can be connected to the same speaker line.
- Small dimensions.
- Low consumption.
- Higher accuracy on impedance measurements.
- Supervision until the last speaker, even in low load speaker lines.
- No return cables.
- 400R/200R configurable load for 19kHz tone.
- Compatible with FG-EVAC-500_AP systems with the latest firmware version.





Technical Specification

Input: 100V or 70V PA line input,

Max. consumption 15mA, 2 Pin Euroblock type 2 positions (400R/200R) ABS, Black RAL9005

Weight: 35gr/1,24oz

Selector:

Enclosure:

Dimensions: 66,3mm x 20mm x 50mm

 $(H \times W \times D) / 2,61 in \times 0,73 in \times 1,97 in$

Accessories : Male Euroblock Connector

MODEL	DESCRIPTION
FG-EVAC-TFL2_AP	End Of Line Device

FG-EVAC-BC_AP CARD FOR BATTERY CHARGER

PRODUCT OVERVIEW

Battery update and activation card EN54-4 certified for **FG-EVAC-500_AP**. Once activated, the card becomes a key for the charger to work permanently.

Features

- Activates EN 54-4 certified function, Emergency Power System (EPS).
- Permanent installation with access control in FG-EVAC-500_AP unit.

MODEL	DESCRIPTION
FG-EVAC-BC_AP	Card For Battery Charger



FG-EVAC-BC_AP hardware: µSD card

Dimensions: 190 x 20 x 140 mm

 $(W \times H \times D) / 7.5" \times 0.8" \times 5.5"$

Gross weight: 0,1 Kg / 0.22 lb

FIREGUARD GLOBAL LTD.

Tel: 00-44-8450751042 Fax: 00-44-8459751043

Email: Info@Fireguard-Uk.com

www.fireguard-Uk.com



Unit 11 · Chancel Industrial Estate · Newhall Street Willenhall · WV13 1NX · United Kingdom













Fire Guard / FG-FVAC-500 AP Accessori